

**OXXA**<sup>®</sup>  
PREMIUM



COMFORT



FLAME  
RETARDENT



SENSITIVITY

# X-WELDER- PRO

## 53-800



### CHARACTERISTICS

- Welding glove made from extremely supple bovine grain leather (0.9-1.0 mm) and cowhide split leather (1.1-1.2 mm)
- Five-fingered design
- Kevlar thread stitching
- Extended hood
- Bovine grain leather palm and cowhide split leather back
- Padded palm for increased comfort and protection and palm reinforcement
- Inserted ("Keystone") thumb for an optimally anatomic design
- Heavy fleece lining
- Suitable for general welding work
- Free of Chromium VI

**Article number: 1.53.800.00**

### SUITABLE FOR ACTIVITIES IN E.G.

- Industry
- Offshore
- Metal industry
- Shipbuilding
- Construction
- Automotive

### COLOUR

Natural/brown

### SIZES

9/L to 11/XXL incl.

### PACKAGING

- 6 pairs per bundle
- 60 pairs per outer box

EN 388:2016  
+A1:2019



3131X

EN 407:2020



413244

EN 12477:2001  
+A1:2005



Type B

**CE 0493**

EN 420:2003+A1:2009

## PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 6 PAIRS (BUNDLE)	EAN CODE 60 PAIRS (OUTER BOX)
9/L	1.53.800.09	8718249067266	8718249067273
10/XL	1.53.800.10	8718249041846	8718249041853
11/XXL	1.53.800.11	8718249041877	8718249041884

## CLARIFICATION OF PICTOGRAMS

EN 388:2016  
+A1:2019



3131X

EN 388:2016  
+A1:2019



abcdef

### Protection against mechanical hazards

- A = Scuff resistance (0-4)
- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13977 (A to F))
- F = Impact resistance (optional) (P = Passed)

## STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

## TESTING INSTITUTE

These gloves are certified by: Centexbel (Notified Body no. 0493), Technologiepark 70, BE 9052 Ghent, Belgium.

## DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: [www.oxxa-safety.com/doc](http://www.oxxa-safety.com/doc)

## YOUR SUPPLIER:

EN 407:2020



413244

EN 407:2020



abcdef

### Heat resistance

- A = Flammability (0-4)
- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiation heat (0-4)
- E = Small droplets of molten metal (0-4)
- F = Large quantities of molten metal (0-4)

Note: X = untested or not applicable

EN 12477:2001  
+A1:2005



Type B

EN 12477:2001  
+A1:2005



Type A/B

### Protective glove for welders

- Type A = for high-temperature welding activities (MIG/MAG)
- Type B = for low-temperature welding activities (TIG)